



SPECIFICATIONS

WEIGHTS

Shipping Weight 2700 lbs. Operating Weight (Full Ballast + Operator) 3200 lbs.

DIMENSIONS

Overall Length 77 in. Overall Height 62 in. Overall Width 40 in. Wheelbase 52.75 in Curb Clearance 9.50 in. Wall Clearance875 in.

CAPACITIES

Fuel 3 gal. Hydraulic Fluid 4 qts. Engine Oil 1.6 pts. Water Tank 34 gal.

STEERING

Type Hydraulic, cylinder, front drum.
Turning Radius 56 in.
Oscillation 24 deg. Total

DRIVE

Drive System Hydrostatic, Internal Direct Drive, Rear Drum, Single Lever, Infinitely Variable Controls. Travel Speed 0-6 mph. EngineHonda Gasoline 20.8 HP

DRUMS

FRONT

Overall Width 30 in. Diameter 20 in. Shell Thickness437 in.

REAR

Overall Width 30 in. Diameter 20 in. Shell Thickness437 in.

DRUM SPRAY SYSTEM

Type Pressurized water w/quick disconnect spray nozzles.

Tank Polyethylene, 34 gal. capacity, 3" fill neck cap w/safety chain, rear mount.

Drum Scrapers Four adjustable, neoprene rubber.

Drum Cocoa Mats One each drum, pivoting.

BRAKES

Service Hydrostatic drive provides dynamic breaking Secondary/Parking Failsafe, Spring applied Hydraulically released, manual switch on console.

VIBRATION SYSTEM-REAR DRUM

Type Hydraulic Direct Drive (Vibe Shaft and Motor in Drum).
Control On-Off Switch on Control Lever.
Frequency 2500 VPM.
Centrifugal Force 4500 lbs. at 2500 VPM.
Total Applied Force 6550 lbs.

STANDARD EQUIPMENT

Instrumentation Fuel Gauge, Hourmeter, Voltmeter, Low Engine Oil Indicator Light. Seat High Back, Bucket Type, Adjustable. Safety Devices Neutral Start Switch, Failsafe Hydraulic Brake. Vandal Protection Lockable fill caps for fuel and hydraulic fluid.

OPTIONAL EQUIPMENT

Back-up Alarm

Special Paint (any Color)
Work Lights
Arm Rests
Vandal Protection Package (locking floor and dash cover)
ROPS (Rollover Protection Structure)
w/seat belt
Manual Hydraulic Release of Motor
Brake
Kubota Diesel 16.6 HP Engine

CONTACT

715-263-2300

INFO@NEWBEUTHLING.COM

WWW.NEWBEUTHLING.COM