

NEW
BEUTHLING

B325

3 TON

**STATIC
COMPACTOR**



SPECIFICATIONS

WEIGHTS

Shipping Weight 3900 lbs.
Operating Weight (Full Ballast
+ Operator) 6000 lbs.

DIMENSIONS

Overall Length 110 in.
Overall Height 71 in.
Overall Width 45 in.
Wheelbase 75 in.
Curb Clearance 12 in.
Wall Clearance 1.75 in.

CAPACITIES

Fuel 8 gal.
Hydraulic Fluid 10 gal.
Engine Oil 4 pts.
Water Tank 50 gal.

STEERING

Type Hydraulic, cylinder, front drum.
Turning Radius 10 ft.
Oscillation 24 deg. Total

DRIVE

Drive System Hydrostatic, Internal
Direct Drive, Rear Drum, Single Lever,
Infinitely Variable Controls.
Travel Speed 0-7 mph.
Engine Kohler 22 HP OHV Twin Cylinder,
Air Cooled, Electric Start, 12 Volt Battery.

BRAKES

Service Hydrostatic drive provides dynamic
breaking
Secondary/Parking Failsafe, Spring applied
Hydraulically released, manual switch on console

DRUMS

FRONT-SPLIT

Type Steel, machined
surface w/ballast fill plug.
Overall Width 33 in.
Diameter 30 in.
Shell Thickness500 in.

REAR

Type Steel, machined
surface.
Overall Width 41 in.
Diameter 30 in.
Shell Thickness500 in.

DRUM SPRAY SYSTEM

Type Pressurized water w/quick
disconnect spray nozzles.
Tank Polyethylene, 50 gal.
capacity, 3" fill neck cap w/safety
chain, rear mount.
Drum Scrapers Four adjustable,
neoprene rubber.
Drum Cocoa Mats One each
drum, pivoting.

STANDARD EQUIPMENT

Instrumentation Fuel Gauge,
Hourmeter, Voltmeter, Low Engine Oil
Indicator Light.
Seat High Back, Bucket Type,
Adjustable.
Safety Devices Neutral Start Switch, \,
Failsafe Hydraulic Brake.
Vandal Protection Lockable fill caps
for fuel and hydraulic fluid.
Transmission By-Pass Towing Valve.
Back-up Alarm

OPTIONAL EQUIPMENT

Special Paint (any Color)
Work Lights
Arm Rests
Vandal Protection Package (locking
floor and dash cover)
ROPS (Rollover Protection Structure)
w/seat belt
Kubota Diesel Engine, water cooled, 3
cylinder

CONTACT

715-263-2300

SALES@NEWBEUTHLING.COM

WWW.NEWBEUTHLING.COM