

# B 1 0 0 STATIC COMPACTOR



# **SPECIFICATIONS**

#### WEIGHTS

Shipping Weight ..... 1800 lbs. Operating Weight (Full Ballast + Operator) ..... 3100 lbs.

#### **DIMENSIONS**

Overall Length ..... 77 in.
Overall Height ..... 63.75 in.
Overall Width ..... 40 in.
Wheelbase ..... 52.75 in
Curb Clearance ..... 9.50 in.
Wall Clearance ..... .875 in.

# **CAPACITIES**

Fuel ..... 3 gal. Hydraulic Fluid ..... 4 gal. Engine Oil ..... 1.5 qts. Water Tank ..... 34 gal.

# **STEERING**

Type ..... Automotive type, mechanical. Turning Radius ..... 60 in. Oscillation ..... 24 deg. Total

#### **DRIVE**

Drive System ..... Hydrostatic, rear drum drive.
Travel Speed ..... 0-5 mph.
Engine ..... Honda Gasoline 20.8 HP

# **DRUMS**

#### **FRONT**

Type ..... Steel, machined surface w/ballast fill plug. Overall Width ..... 30 in. Diameter ..... 20 in. Shell Thickness ..... .500 in.

#### REAR

Type ..... Steel, machined surface w/ballast fill plug. Overall Width ..... 37 in. Diameter ..... 24 in. Shell Thickness ..... 500 in.

# **DRUM SPRAY SYSTEM**

Type ..... Gravity w/dual brass ball valves.

Tank ..... Polyethylene, 34 gal. capacity, 3" fill neck cap w/safety chain, rear mount.

Drum Scrapers ..... Four adjustable, neoprene rubber.

Drum Cocoa Mats ..... One each drum, pivoting.

# STANDARD EQUIPMENT

Instrumentation ..... Hourmeter,
Voltmeter, Low Engine Oil Indicator Light.
Seat ..... High Back, Bucket Type,
Adjustable.
Safety Devices ...... Neutral Start Switch.
Transmission By-Pass ..... Towing Valve.
Vandal Protection ..... Lockable fill caps

for fuel and hydraulic fluid.

Tie Downs ..... (6) for transporting.

Back-up Alarm

# **OPTIONAL EQUIPMENT**

Special Paint (any Color)
Work Lights
Arm Rests
Vandal Protection Package (locking floor and dash cover)
ROPS (Rollover Protection Structure)
w/seat belt
Sight Gauge (hydraulic reservoir)
Pressurized Drum Spray
Kubota Diesel 15.6 HP Engine

#### **BRAKES**

Service ..... Hydrostatic, rear drum drive. Secondary/Parking ..... Mechanical band type parking brake on rear drum, adjustable brake lever.



715-263-2300 SALES@NEWBEUTHLING.COM WWW.NEWBEUTHLING.COM