



B200

2 TON

STATIC COMPACTOR



SPECIFICATIONS

WEIGHTS

Shipping Weight 2500 lbs.
Operating Weight (Full Ballast
+ Operator) 4150 lbs.

DIMENSIONS

Overall Length 97 in.
Overall Height 65 in.
Overall Width 44 in.
Wheelbase 66.5 in
Curb Clearance 11 in.
Wall Clearance875 in.

CAPACITIES

Fuel 5 gal.
Hydraulic Fluid 4 gal.
Engine Oil 4 pts.
Water Tank 50 gal.

STEERING

Type Automotive type, mechanical.
Turning Radius 72 in.
Oscillation 24 deg. Total

DRIVE

Drive System Hydrostatic.
Travel Speed 0-5 mph.
Engine Honda Gasoline 22.1 HP

BRAKES

Service Hydrostatic drive provides
dynamic breaking
Secondary/Parking Mechanical
band type parking brake on rear
drum, adjustable brake lever.

DRUMS

FRONT

Type Steel, machined
surface w/ballast fill plug.
Overall Width 30 in.
Diameter 24 in.
Shell Thickness500 in.

REAR

Type Steel, machined
surface w/ballast fill plug.
Overall Width 41 in.
Diameter 28 in.
Shell Thickness500 in.

DRUM SPRAY SYSTEM

Type Gravity w/dual brass ball
valves.
Tank Polyethylene, 50 gal. capacity,
3" fill neck cap w/safety chain, rear
mount.
Drum Scrapers Four adjustable,
neoprene rubber.
Drum Cocoa Mats One each drum,
pivoting.

STANDARD EQUIPMENT

Instrumentation Hourmeter,
Voltmeter, Low Engine Oil Indicator Light.
Seat High Back, Bucket Type,
Adjustable.
Safety Devices Neutral Start Switch.
Transmission By-Pass Control within
pump to "Freewheel unit"
Vandal Protection Lockable fill caps
for fuel and hydraulic fluid.
Tie Downs (6) for transporting.
Back-up Alarm

OPTIONAL EQUIPMENT

Special Paint (any Color)
Work Lights
Arm Rests
Vandal Protection Package (locking
floor and dash cover)
ROPS (Rollover Protection Structure)
w/seat belt
Sight Gauge (hydraulic reservoir)
Pressurized Drum Spray
Kubota Diesel 22.5 HP Engine

CONTACT

715-263-2300

SALES@NEWBEUTHLING.COM

WWW.NEWBEUTHLING.COM