



B60

1-TON

STATIC COMPACTOR



SPECIFICATIONS

WEIGHTS

Shipping Weight 1500 lbs.
Operating Weight (Full Ballast
+ Operator) 2400 lbs.

DIMENSIONS

Overall Length 72 in.
Overall Height 58 in.
Overall Width 38 in.
Wheelbase 50.75 in
Curb Clearance 8.50 in.
Wall Clearance875 in.

CAPACITIES

Fuel 1.75 gal.
Hydraulic Fluid 1 gal.
Engine Oil 1.16 qts.
Water Tank 25 gal.

STEERING

Type Automotive type, mechanical.
Turning Radius 56 in.
Oscillation 24 deg. Total

DRIVE

Drive System Hydrostatic
Travel Speed 0-5 mph.
Engine Honda 11 HP OHV Single
Cylinder, Electric Start (in addition to
pull start under cover), Low Oil Alert
System, 12 Volt Battery.

DRUMS

FRONT

Type Steel, machined
surface w/ballast fill plug.
Overall Width 28 in.
Diameter 18 in.
Shell Thickness500 in.

REAR

Type Steel, machined
surface w/ballast fill plug.
Overall Width 34.75 in.
Diameter 22 in.
Shell Thickness500 in.

DRUM SPRAY SYSTEM

Type Gravity w/dual brass ball
valves.
Tank Polyethylene, 25 gal. capacity,
3" fill neck cap w/safety chain, rear
mount.
Drum Scrapers Two steel scrapers,
spring loaded.
Drum Cocoa Mats One each drum,
pivoting.

STANDARD EQUIPMENT

Brakes Dynamic w/mechanical
band type parking brake on rear
drum, adjustable brake lever.
Transmission By-Pass Control
within pump to "Freewheel unit."
Gauges Hourmeter
Safety Devices Neutral Start
Switch.
Back-up Alarm

OPTIONAL EQUIPMENT

Special Paint
Voltage Gauge
Vandal Protection Package
(locking floor and dash cover)
ROPS (Rollover Protection
Structure)

CONTACT

715-263-2300

SALES@NEWBEUTHLING.COM

WWW.NEWBEUTHLING.COM