



SPECIFICATIONS

WEIGHTS

Shipping Weight 3100 lbs. Operating Weight (Full Ballast + Operator) 4200 lbs.

DIMENSIONS

Overall Length 97 in. Overall Height 65 in. Overall Width 44 in. Wheelbase 65.5 in Curb Clearance 11 in. Wall Clearance75 in.

CAPACITIES

Fuel 5 gal. Hydraulic Fluid 4 gal. Engine Oil 2.1 qts. Water Tank 50 gal.

STEERING

Type Hydraulic, cylinder, front drum. Turning Radius 68 in. Oscillation 24 deg. Total

DRIVE

Drive System Hydrostatic, Internal Direct Drive, Rear Drum, Single Lever, Infinitely Variable Controls.

Travel Speed 0-6 mph. Engine Honda Gasoline 22.1 HP

DRUMS

FRONT

Overall Width 30 in. Diameter 24 in. Shell Thickness437 in.

REAR

Overall Width 40 in. Diameter 28 in. Shell Thickness500 in.

DRUM SPRAY SYSTEM

Type Pressurized water w/quick disconnect spray nozzles.

Tank Polyethylene, 50 gal. capacity, 3" fill neck cap w/safety chain, rear mount.

Drum Scrapers Four adjustable, neoprene rubber.
Drum Cocoa Mats One each drum,

Drum Cocoa Mats One each drum pivoting.

BRAKES

Service Hydrostatic drive provides dynamic breaking Secondary/Parking Failsafe, Spring applied Hydraulically released, manual switch on console.

VIBRATION SYSTEM-REAR DRUM

Type Hydraulic Direct Drive (Vibe Shaft and Motor in Drum).

Control On-Off Switch on Control Lever.

Frequency 2500 VPM

Frequency 2500 VPM. Centrifugal Force 6000 lbs. at 2500 VPM. Total Applied Force 9500 lbs.

STANDARD EQUIPMENT

Voltmeter, Low Engine Oil Indicator Light.
Seat High Back, Bucket Type, Adjustable.
Safety Devices Neutral Start Switch,
Failsafe Hydraulic Brake.
Vandal Protection Lockable fill caps for fuel and hydraulic fluid.

Instrumentation Fuel Gauge, Hourmeter,

OPTIONAL EQUIPMENT

Back-up Alarm

Special Paint (any Color)
Work Lights
Arm Rests
Vandal Protection Package (locking floor and dash cover)
ROPS (Rollover Protection Structure)
w/seat belt
Fuel Gauge
Kubota Diesel 22.5 HP Engine

CONTACT.

715-263-2300

SALES@NEWBEUTHLING.COM

WWW.NEWBEUTHLING.COM