



B105

1-1/2 TON STATIC COMPACTOR



SPECIFICATIONS

WEIGHTS

Shipping Weight 2,250 lbs.
Operating Weight (Full Ballast + Operator) 3,000 lbs.

DIMENSIONS

Overall Length 77 in.
Overall Height 62 in.
Overall Width 40 in.
Wheelbase 52.75 in
Curb Clearance 9.50 in.
Wall Clearance750 in.

CAPACITIES

Fuel 3 gal.
Hydraulic Fluid 4 gal.
Engine Oil 1.6 qts.
Water Tank 34 gal.

STEERING

Type Hydraulic power, cylinder-front drum
Turning Radius 60 in.
Oscillation 24 deg. Total

DRIVE

Drive System Hydrostatic, Internal Direct Drive, Rear Drum Single Lever, Infinitely Variable Controls
Travel Speed 0-6 mph
Engine Honda GX630 20.8hp

BRAKES

Service Hydrostatic, rear drum drive.
Secondary/Parking Mechanical band type parking brake on rear drum, adjustable brake lever.

DRUMS

FRONT

Overall Width 30 in.
Diameter 20 in.
Shell Thickness437 in.

REAR

Overall Width 37.5 in.
Diameter 24 in.
Shell Thickness437 in.

DRUM SPRAY SYSTEM

Type Pressurized water w/ quick disconnect spray nozzles
Tank Polyethylene Plastic 3" fill neck, cap w/ safety chain rear, 34 gal. capacity
Drum Scrapers Four adjustable, rubber
Drum Cocoa Mats One each drum, pivoting

STANDARD EQUIPMENT

Instrumentation Hourmeter, Voltmeter, Low Engine Oil Indicator Light
Seat High Back, Bucket Type, Adjustable
Safety Devices Neutral Start Switch, Failsafe Hydraulic Brake
Work Lights
Arm Rests
Pressure Water

OPTIONAL EQUIPMENT

Special Paint (any Color)
ROPS (Rollover Protection Structure) w/seat belt
Sight Gauge (hydraulic reservoir)
Kubota Diesel 15.6 HP Engine

CONTACT

715-263-2300

SALES@NEWBEUTHLING.COM

WWW.NEWBEUTHLING.COM