



B100

1-1/2 TON

STATIC COMPACTOR



SPECIFICATIONS

WEIGHTS

Shipping Weight 1800 lbs.
Operating Weight (Full Ballast
+ Operator) 3100 lbs.

DIMENSIONS

Overall Length 77 in.
Overall Height 63.75 in.
Overall Width 40 in.
Wheelbase 52.75 in.
Curb Clearance 9.50 in.
Wall Clearance875 in.

CAPACITIES

Fuel 3 gal.
Hydraulic Fluid 2.5 gal.
Engine Oil 1.5 qts.
Water Tank 34 gal.

STEERING

Type Automotive type,
mechanical.
Turning Radius 60 in.
Oscillation 24 deg. Total

DRIVE

Drive System Hydrostatic, rear
drum drive.
Travel Speed 0-5 mph.
Engine Honda Gasoline 20.8
HP

BRAKES

Service Hydrostatic, rear drum drive.
Secondary/Parking Mechanical band
type parking brake on rear drum,
adjustable brake lever.

DRUMS

FRONT

Type Steel, machined
surface w/ballast fill plug.
Overall Width 30 in.
Diameter 20 in.
Shell Thickness375 in.

REAR

Type Steel, machined
surface w/ballast fill plug.
Overall Width 37 in.
Diameter 24 in.
Shell Thickness375 in.

DRUM SPRAY SYSTEM

Type Pressurized water w/ quick
disconnect spray nozzles.
Tank Polyethylene, 34 gal.
capacity, 3" fill neck cap, rear mount.
Drum Scrapers Four adjustable,
rubber.
Drum Cocoa Mats One each
drum, pivoting.

STANDARD EQUIPMENT

Instrumentation Hourmeter,
Voltmeter, Low Engine Oil Indicator
Light
Seat High Back, Bucket Type,
Adjustable w/ Arm Rests
Safety Devices Neutral Start
Switch, Failsafe Hydraulic Brake, Work
Lights, and Back-up Alarm
Pressurized Drum Spray

OPTIONAL EQUIPMENT

Special Paint (any Color)
Vandal Protection Package (locking
floor and dash cover)
ROPS (Rollover Protection Structure)
w/seat belt
Sight Gauge (hydraulic reservoir)
Kubota Diesel 15.6 HP Engine

CONTACT

715-263-2300

SALES@NEWBEUTHLING.COM

WWW.NEWBEUTHLING.COM