



B105

1-1/2 TON

STATIC COMPACTOR



SPECIFICATIONS

WEIGHTS

Shipping Weight 2,250 lbs.
Operating Weight (Full Ballast + Operator) 3,000 lbs.

DIMENSIONS

Overall Length 77 in.
Overall Height 62 in.
Overall Width 40 in.
Wheelbase 52.75 in.
Curb Clearance 9.50 in.
Wall Clearance750 in.

CAPACITIES

Fuel 3 gal.
Hydraulic Fluid 3 gal.
Engine Oil 1.6 qts.
Water Tank 34 gal.

STEERING

Type Hydraulic power, cylinder-front drum
Turning Radius 56 in.
Oscillation 24 deg. Total

DRIVE

Drive System Hydrostatic, Internal Direct Drive, Rear Drum Single Lever, Infinitely Variable Controls
Travel Speed 0-6 mph
Engine Honda GX630 20.8hp

DRUMS

FRONT

Overall Width 30 in.
Diameter 20 in.
Shell Thickness375 in.

REAR

Overall Width 36 in.
Diameter 24 in.
Shell Thickness500 in.

DRUM SPRAY SYSTEM

Type Pressurized water w/ quick disconnect spray nozzles
Tank Polyethylene Plastic 3" fill neck, rear, 34 gal. capacity
Drum Scrapers Four adjustable, rubber
Drum Cocoa Mats One each drum, pivoting

BRAKES

Service Hydrostatic drive provides dynamic breaking
Secondary/Parking Failsafe, Spring applied Hydraulically released, manual switch on console.

STANDARD EQUIPMENT

Instrumentation Hourmeter, Voltmeter, Low Engine Oil Indicator Light
Seat High Back, Bucket Type, Adjustable w/ Arm Rests
Safety Devices Neutral Start Switch, Failsafe Hydraulic Brake, Work Lights, and Back-up Alarm
Pressurized Drum Spray

OPTIONAL EQUIPMENT

Special Paint (any Color)
Seat Base with Strobe Light
Sight Gauge (hydraulic reservoir)
Kubota Diesel 15.6 HP Engine
Vandal Protection Package

CONTACT

715-263-2300

SALES@NEWBEUTHLING.COM

WWW.NEWBEUTHLING.COM