



B305

2-1/4 TON

VIBRATORY COMPACTOR



SPECIFICATIONS

WEIGHTS

Shipping Weight 3100 lbs.
Operating Weight (Full Ballast
+ Operator) 4200 lbs.

DIMENSIONS

Overall Length 97 in.
Overall Height 65 in.
Overall Width 44 in.
Wheelbase 65.5 in.
Curb Clearance 11 in.
Wall Clearance75 in.

CAPACITIES

Fuel 5 gal.
Hydraulic Fluid 4 gal.
Engine Oil 2.1 qts.
Water Tank 50 gal.

STEERING

Type Hydraulic,
cylinder, front drum.
Turning Radius 68 in.
Oscillation 24 deg. Total

DRIVE

Drive System Hydrostatic,
Internal Direct Drive, Rear Drum,
Single Lever, Infinitely Variable
Controls.
Travel Speed 0-6 mph.
Engine Honda Gasoline 22.1 HP

DRUMS

FRONT

Overall Width 30 in.
Diameter 24 in.
Shell Thickness375 in.

REAR

Overall Width 40 in.
Diameter 28 in.
Shell Thickness500 in.

DRUM SPRAY SYSTEM

Type Pressurized water w/quick
disconnect spray nozzles.
Tank Polyethylene, 50 gal.
capacity, 3" fill neck, rear mount.
Drum Scrapers Four adjustable,
rubber.
Drum Cocoa Mats One each
drum, pivoting.

BRAKES

Service Hydrostatic drive
provides dynamic breaking
Secondary/Parking Failsafe,
Spring applied Hydraulically
released, manual switch on
console.

VIBRATION SYSTEM-REAR DRUM

Type Hydraulic Direct Drive (Vibe Shaft
and Motor in Drum).
Control On-Off Switch on Control Lever.
Frequency 2500 VPM.
Centrifugal Force 6000 lbs. at 2500
VPM.
Total Applied Force 9500 lbs.

STANDARD EQUIPMENT

Instrumentation Fuel Gauge,
Hourmeter, Voltmeter, Low Engine Oil
Indicator Light.
Seat High Back, Bucket Type,
Adjustable with Arm Rests
Safety Devices Neutral Start Switch,
Work Lights, Back-up Alarm, and Failsafe
Hydraulic Brake.

OPTIONAL EQUIPMENT

Special Paint (any Color)
Vandal Protection Package (locking
floor and dash cover)
Seat Base with Strobe Light
Kubota Diesel 22.5 HP Engine

CONTACT

SALES@NEWBEUTHLING.COM

WWW.NEWBEUTHLING.COM