

NEW BEUTHLING

SMOOTH RESULTS

Our rollers evenly distribute asphalt, resulting in an extremely smooth surface and eliminating air pockets. New Beuthling machines are known for their consistently smooth results.

SPLIT DRUM ADVANTAGE

New Beuthling asphalt rollers feature a split front drum design, enhancing maneuverability and reducing the risk of asphalt displacement during turns, ensuring a more uniform compaction.

SIMPLER IS BETTER

Our rollers offer the right balance of power and precision for projects such as driveways, pedestrian walkways, and bike paths.



CUSTOMER TESTIMONIALS

“The split drum doesn’t stretch, pull or twist the asphalt.”

“When it is hot, the Beuthling roller leaves a like glass finish.”

“We have been using Beuthling rollers, the B100/B200s since the early 90s. We believe it’s one of the best static finish rollers out there!”

“Split drums almost anyone can roll, the articulated rollers you need to be experienced.”

“We love the maneuverability of a Beuthling. Handles straight aways, corners and tight fits better than any other roller of comparable size on the market.”

CONTACT US

715-263-2300

SALES@NEWBEUTHLING.COM



LEARN
MORE

NEW
BEUTHLING

B60

1-TON STATIC COMPACTOR



SPECIFICATIONS

WEIGHTS

Shipping Weight 1500 lbs.
Operating Weight (Full Ballast + Operator) 2400 lbs.

DIMENSIONS

Overall Length 72 in.
Overall Height 58 in.
Overall Width 38 in.
Wheelbase 50.75 in
Curb Clearance 8.50 in.
Wall Clearance875 in.

CAPACITIES

Fuel 1.75 gal.
Hydraulic Fluid 1 gal.
Engine Oil 1.16 qts.
Water Tank 25 gal.

STEERING

Type Automotive type, mechanical.
Turning Radius 56 in.
Oscillation 24 deg. Total

DRIVE

Drive System Hydrostatic
Travel Speed 0-5 mph.
Engine Honda 11 HP OHV Single Cylinder, Electric Start (in addition to pull start under cover), Low Oil Alert System, 12 Volt Battery.

DRUMS

FRONT

Type Steel, machined surface w/ballast fill plug.
Overall Width 28 in.
Diameter 18 in.
Shell Thickness375in.

REAR

Type Steel, machined surface w/ballast fill plug.
Overall Width 34.75 in.
Diameter 22 in.
Shell Thickness375 in.

DRUM SPRAY SYSTEM

Type Gravity w/dual brass ball valves.
Tank Polyethylene, 25 gal. capacity, 3" fill neck, rear mount.
Drum Scrapers Two steel scrapers, spring loaded.
Drum Cocoa Mats One each drum, pivoting.

STANDARD EQUIPMENT

Brakes Dynamic w/mechanical band type parking brake on rear drum, adjustable brake lever.
Transmission By-Pass Control within pump to "Freewheel unit."
Instrumentation Hourmeter
Safety Devices Neutral Start Switch, Back-up Alarm.

OPTIONAL EQUIPMENT

Special Paint (any color)
Vandal Protection Package (locking floor and dash cover)
Seat Base with Strobe Light

MSRP \$21,645

CONTACT

715-263-2300

SALES@NEWBEUTHLING.COM

WWW.NEWBEUTHLING.COM

NEW
BEUTHLING

B100

1-1/2 TON STATIC COMPACTOR



SPECIFICATIONS

WEIGHTS

Shipping Weight 1800 lbs.
Operating Weight (Full Ballast + Operator) 3100 lbs.

DIMENSIONS

Overall Length 77 in.
Overall Height 63.75 in.
Overall Width 40 in.
Wheelbase 52.75 in
Curb Clearance 9.50 in.
Wall Clearance875 in.

CAPACITIES

Fuel 3 gal.
Hydraulic Fluid 2.5 gal.
Engine Oil 1.5 qts.
Water Tank 34 gal.

STEERING

Type Automotive type, mechanical.
Turning Radius 60 in.
Oscillation 24 deg. Total

DRIVE

Drive System Hydrostatic, rear drum drive.
Travel Speed 0-5 mph.
Engine Honda Gasoline 20.8 HP

BRAKES

Service Hydrostatic, rear drum drive.
Secondary/Parking Mechanical band type parking brake on rear drum, adjustable brake lever.

DRUMS

FRONT

Type Steel, machined surface w/ballast fill plug.
Overall Width 30 in.
Diameter 20 in.
Shell Thickness375 in.

REAR

Type Steel, machined surface w/ballast fill plug.
Overall Width 37 in.
Diameter 24 in.
Shell Thickness375 in.

DRUM SPRAY SYSTEM

Type Pressurized water w/ quick disconnect spray nozzles.
Tank Polyethylene, 34 gal. capacity, 3" fill neck cap, rear mount.
Drum Scrapers Four adjustable, rubber.
Drum Cocoa Mats One each drum, pivoting.

STANDARD EQUIPMENT

Instrumentation Hourmeter, Voltmeter, Low Engine Oil Indicator Light
Seat High Back, Bucket Type, Adjustable w/ Arm Rests
Safety Devices Neutral Start Switch, Failsafe Hydraulic Brake, Work Lights, and Back-up Alarm
Pressurized Drum Spray

OPTIONAL EQUIPMENT

Special Paint (any Color)
Vandal Protection Package (locking floor and dash cover)
Seat Base with Strobe Light
Sight Gauge (hydraulic reservoir)
Kubota Diesel 15.6 HP Engine

MSRP \$26,535 (Gas)
\$34,878 (Diesel)

CONTACT

715-263-2300

SALES@NEWBEUTHLING.COM

WWW.NEWBEUTHLING.COM

NEW BEUTHLING

B105

1-1/2 TON STATIC COMPACTOR



SPECIFICATIONS

WEIGHTS

Shipping Weight 2,250 lbs.
Operating Weight (Full Ballast + Operator) 3,000 lbs.

DIMENSIONS

Overall Length 77 in.
Overall Height 62 in.
Overall Width 40 in.
Wheelbase 52.75 in
Curb Clearance 9.50 in.
Wall Clearance750 in.

CAPACITIES

Fuel 3 gal.
Hydraulic Fluid 3 gal.
Engine Oil 1.6 qts.
Water Tank 34 gal.

STEERING

Type Hydraulic power, cylinder-front drum
Turning Radius 56 in.
Oscillation 24 deg. Total

DRIVE

Drive System Hydrostatic, Internal Direct Drive, Rear Drum Single Lever, Infinitely Variable Controls
Travel Speed 0-6 mph
Engine Honda GX630 20.8hp

DRUMS

FRONT

Overall Width 30 in.
Diameter 20 in.
Shell Thickness375 in.

REAR

Overall Width 36 in.
Diameter 24 in.
Shell Thickness500 in.

DRUM SPRAY SYSTEM

Type Pressurized water w/ quick disconnect spray nozzles
Tank Polyethylene Plastic 3" fill neck, rear, 34 gal. capacity
Drum Scrapers Four adjustable, rubber
Drum Cocoa Mats One each drum, pivoting

BRAKES

Service Hydrostatic drive provides dynamic breaking
Secondary/Parking Failsafe, Spring applied Hydraulically released, manual switch on console.

STANDARD EQUIPMENT

Instrumentation Hourmeter, Voltmeter, Low Engine Oil Indicator Light
Seat High Back, Bucket Type, Adjustable w/ Arm Rests
Safety Devices Neutral Start Switch, Failsafe Hydraulic Brake, Work Lights, and Back-up Alarm
Pressurized Drum Spray

OPTIONAL EQUIPMENT

Special Paint (any Color)
Seat Base with Strobe Light
Sight Gauge (hydraulic reservoir)
Kubota Diesel 15.6 HP Engine
Vandal Protection Package

MSRP \$30,757 (Gas)
\$38,878 (Diesel)

CONTACT

715-263-2300

SALES@NEWBEUTHLING.COM

WWW.NEWBEUTHLING.COM

NEW BEUTHLING

B155

1-1/2 TON VIBRATORY COMPACTOR



SPECIFICATIONS

WEIGHTS

Shipping Weight 2700 lbs.
Operating Weight (Full Ballast + Operator) 3200 lbs.

DIMENSIONS

Overall Length 77 in.
Overall Height 62 in.
Overall Width 40 in.
Wheelbase 52.75 in
Curb Clearance 9.50 in.
Wall Clearance875 in.

CAPACITIES

Fuel 3 gal.
Hydraulic Fluid 3 gal.
Engine Oil 1.6 qts.
Water Tank 34 gal.

STEERING

Type Hydraulic, cylinder, front drum.
Turning Radius 56 in.
Oscillation 24 deg. Total

DRIVE

Drive System Hydrostatic, Internal Direct Drive, Rear Drum, Single Lever, Infinitely Variable Controls.
Travel Speed 0-6 mph.
Engine Honda Gasoline 20.8 HP

DRUMS

FRONT

Overall Width 30 in.
Diameter 20 in.
Shell Thickness375 in.

REAR

Overall Width 36 in.
Diameter 24 in.
Shell Thickness500 in.

DRUM SPRAY SYSTEM

Type Pressurized water w/quick disconnect spray nozzles.
Tank Polyethylene, 34 gal. capacity, 3" fill neck cap, rear mount.
Drum Scrapers Four adjustable, rubber.
Drum Cocoa Mats One each drum, pivoting.

BRAKES

Service Hydrostatic drive provides dynamic breaking
Secondary/Parking Failsafe, Spring applied Hydraulically released, manual switch on console.

VIBRATION SYSTEM-REAR DRUM

Type Hydraulic Direct Drive (Vibe Shaft and Motor in Drum).
Control On-Off Switch on Control Lever.
Frequency 2500 VPM.
Centrifugal Force 4500 lbs. at 2500 VPM.
Total Applied Force 6550 lbs.

STANDARD EQUIPMENT

Instrumentation Fuel Gauge, Hourmeter, Voltmeter, Low Engine Oil Indicator Light.
Seat High Back, Bucket Type, Adjustable w/ Arm Rests.
Safety Devices Neutral Start Switch, Work Lights, Back-up Alarm, and Failsafe Hydraulic Brake.

OPTIONAL EQUIPMENT

Special Paint (any Color)
Vandal Protection Package (locking floor and dash cover)
Seat Base with Strobe Light
Kubota Diesel 16.6 HP Engine

MSRP \$35,258 (Gas)
\$43,390 (Diesel)

CONTACT

715-263-2300

SALES@NEWBEUTHLING.COM

WWW.NEWBEUTHLING.COM

NEW
BEUTHLING

B305

2-1/4 TON
VIBRATORY
COMPACTOR



SPECIFICATIONS

WEIGHTS

Shipping Weight 3100 lbs.
Operating Weight (Full Ballast + Operator) 4200 lbs.

DIMENSIONS

Overall Length 97 in.
Overall Height 65 in.
Overall Width 44 in.
Wheelbase 65.5 in
Curb Clearance 11 in.
Wall Clearance75 in.

CAPACITIES

Fuel 5 gal.
Hydraulic Fluid 4 gal.
Engine Oil 2.1 qts.
Water Tank 50 gal.

STEERING

Type Hydraulic, cylinder, front drum.
Turning Radius 68 in.
Oscillation 24 deg. Total

DRIVE

Drive System Hydrostatic, Internal Direct Drive, Rear Drum, Single Lever, Infinitely Variable Controls.
Travel Speed 0-6 mph.
Engine Honda Gasoline 22.1 HP

DRUMS

FRONT

Overall Width 30 in.
Diameter 24 in.
Shell Thickness375 in.

REAR

Overall Width 40 in.
Diameter 28 in.
Shell Thickness500 in.

DRUM SPRAY SYSTEM

Type Pressurized water w/quick disconnect spray nozzles.
Tank Polyethylene, 50 gal. capacity, 3" fill neck, rear mount.
Drum Scrapers Four adjustable, rubber.
Drum Cocoa Mats One each drum, pivoting.

BRAKES

Service Hydrostatic drive provides dynamic breaking
Secondary/Parking Failsafe, Spring applied Hydraulically released, manual switch on console.

MSRP \$41,193 (Gas)
 \$50,480 (Diesel)

VIBRATION SYSTEM-REAR DRUM

Type Hydraulic Direct Drive (Vibe Shaft and Motor in Drum).
Control On-Off Switch on Control Lever.
Frequency 2500 VPM.
Centrifugal Force 6000 lbs. at 2500 VPM.
Total Applied Force 9500 lbs.

STANDARD EQUIPMENT

Instrumentation Fuel Gauge, Hourmeter, Voltmeter, Low Engine Oil Indicator Light.
Seat High Back, Bucket Type, Adjustable with Arm Rests
Safety Devices Neutral Start Switch, Work Lights, Back-up Alarm, and Failsafe Hydraulic Brake.

OPTIONAL EQUIPMENT

Special Paint (any Color)
Vandal Protection Package (locking floor and dash cover)
Seat Base with Strobe Light
Kubota Diesel 22.5 HP Engine

CONTACT

715-263-2300

SALES@NEWBEUTHLING.COM

WWW.NEWBEUTHLING.COM